

HIGH PRESSURE PAINT HOSE

DATA SHEET 102-



Type: **PA**

POLYAMIDE
WIRE BRAID
POLYURETHANE



POLYAMIDE
WIRE BRAID
INTERLAYER
POLYURETHANE

CONSTRUCTION:

- Inner tube : Polyamide
- Reinforcement : high tensile brass plated carbon steel
- Cover : Polyurethane

APPLICATION

- High pressure painting
- High pressure hydraulics
- High pressure solvent, paint, chemicals
- High pressure water-jetting

TEMPERATURE RANGE

-40°C to 98°C, -40°F to 208°F

PROPERTIES

- Excellent flexibility and flex-fatigue
- Extreme abrasion resistance
- Static free, 100% conductive
- Low diffusion rate and low flow resistance
- UV and Ozone resistant
- Suitable for all mineral based hydraulic oils
- Suitable for reusable couplings

TECHNICAL SPECIFICATIONS : EXITFLEX TYPE **PA1.X** – ONE WIRE BRAID

HOSE TYPE		PA 1.2	PA 1.3	PA1.4	PA 1.5	PA 1.6	PA 1.8
NOMINAL BORE METRIC		3	4	6	8	10	12
HOSE I.D. INCH		1/8"	3/16"	1/4"	5/16"	3/8"	1/2"
HOSE I.D. MILLIMETER		3,2	4,8	6,4	8,0	9,6	12,7
HOSE O.D. MILLIMETER		7,0	9,3	11,7	13,8	15,2	18,5
MAX.OPERATING PRESSURE	In Bar	350	350	325	275	250	200
	In PSI	5'100	5'100	4'700	4'000	3'600	2'900
MINIMUM BURST PRESSURE @ 20°C	In Bar	1'400	1'400	1'300	1'100	1'000	800
	In PSI	20'400	20'400	18'800	16'000	14'400	11'600
MINIMUM BEND RADIUS IN MILLIMETER		25	35	45	50	60	70
NOMINAL WEIGHT in GRAMS PER METER		60	105	160	200	230	310

TECHNICAL SPECIFICATIONS : EXITFLEX TYPE **PA2.X** – TWO WIRE BRAID

HOSE TYPE		PA 2.4	PA2.5	PA 2.6	PA 2.8	PA 2.12
NOMINAL BORE METRIC		6	8	10	12	20
HOSE I.D. INCH		1/4"	5/16"	3/8"	1/2"	3/4"
HOSE I.D. MILLIMETER		6,4	8,0	9,6	12,7	19,0
HOSE O.D. MILLIMETER		13,8	15,5	17,5	21,5	30
MAX.OPERATING PRESSURE	In Bar	450	425	425	325	235
	In PSI	6'500	6'150	6'150	4'700	3'400
MINIMUM BURST PRESSURE @ 20°C	In Bar	1'800	1'700	1'700	1'300	940
	In PSI	26'000	24'600	24'600	18'800	13'600
MINIMUM BEND RADIUS IN MILLIMETER		50	60	70	85	110
NOMINAL WEIGHT in GRAMS PER METER		260	320	420	560	900

Note: UPON SPECIAL REQUEST

- HOSE ASSEMBLIES are all fitted with bi-chromated steel couplings swaged permanently to the hose
- STAINLESS STEEL COUPLINGS available on request
- STANDARD COLOR : is black or blue, others available in large quantities at customers request
- BULK HOSE : is available on non returnable reel

All recommendations and suggestions appearing in this bulletin concerning the use of our products are based upon tests and data believed to be reliable. Since the actual use by others is beyond our control, no guarantee, expressed or implied, is made by Exit S.A., its subsidiaries, affiliates and distributors, as to the effects of such use or the results to be obtained, nor is any information to be construed as a recommendation to infringe any patent.